



2-Stage Horizontal Rotor

Our patented swing-out horizontal rotor design incorporates a unique test tube holder that produces the ideal horizontally separated samples.





642B

HORIZONTAL SINGLE-SPEED CENTRIFUGE

Part # 00-016-009-001

Produce high-quality sample separations at our most affordable price. The 642B's simple, single-speed settings and adjustable mechanical timer meet a variety of blood specimen preparation needs. The unique rotor design allows for horizontal processing with minimal maintenance and no hassle.

A Great Value

Unbeatable quality for any budget. Each unit arrives ready to run with a rotor, tube holders, and 2-year warranty included in the affordable price.

Easy to Use

The 642B offers powerful single-speed processing with an easily adjustable mechanical timer. Set to run at a constant 1,600 xg, the 642B allows selection of cycle time from 1 to 30 minutes.

Cool Operation

Unique design of the motor housing and rotation chamber keeps specimens cool during processing.

Built to Last

Reinforced components and brushless motor provide years of maintenance-free operation. The clear, shatterproof lid enhances lab safety.

For Better Repeatability

When consistency is key, please consider the single-speed, electronic **642E**. The 642E is the world's best-selling clinical laboratory centrifuge and features a simple, two-button interface and preset runtime for all common chemistry needs.



Model 642E

Applications	Max Speed	Max Capacity	Included	Warranty
Chemistry, Coag, PPP	1,600 xg Max RCF 3,380 Max RPM	6 x 75-100 mm 3-10 mL	Horizontal Rotor, Tube Holders	2 years Rotor: lifetime warranty

642B Centrifuge

642B	Specifications	642B
00-016-009-001	Sound level	65 dBA
7713079 (6 qty)	Dimensions (W x D x H)	12 x 14 x 9 in
02 0 0007 0001		30 x 36 x 23 cm
03-0-0007-0001	Weight	11 lbs (5 kg)
03-0-0007-0002	Max RPM	3380 RPM
03-0-0007-0006	Max G-Force	1600 xg
	00-016-009-001 7713079 (6 qty) 03-0-0007-0001 03-0-0007-0002	00-016-009-001 Sound level 7713079 (6 qty) Dimensions (W x D x H) 03-0-0007-0001 Weight 03-0-0007-0002 Max RPM

Power

115 V - 50/60 Hz

Safely observe samples through o the clear, shatterproof lid QR code for easy access to support videos, manuals, and **MODEL** 642B Orucker Diagnostics Reinforced guard bowl and ~ more Time (Min.) brushless motor for quiet, Easily adjustable mechanical maintenance-free operation timer can be set from 1 to 30 minutes Consistent processing at 1,600 xg (3,400 RPM)

OTHER DRUCKER MODELS

